



SELECT 1000

100% ACRYLIC EXTERIOR HOUSEPAINT

459X SERIES – FLAT FINISH

469X SERIES – EGGSHELL FINISH

479X SERIES – SATIN FINISH

General Description

A high quality 100% acrylic house paint formulated for professionals. Provides a durable, fade resistant finish on both residential and commercial buildings. Self priming over previously painted substrates in good sound condition.

Where to Use

New or previously painted or primed exterior substrates, including most wood siding, shakes, cement board, hardboard, steel, vinyl, aluminum, brick, and masonry. **Some exterior vinyl and PVC products have specific painting recommendations with regards to LRV (Light Reflective Values). In some cases a color with an LRV <55 may cause the product to warp. Always check with the manufacturer before selecting color.**

Physical Product Data ^o	4590 (Flat)	4690 (Eggshell)	4790 (Satin)
Product Type	100% Acrylic	100% Acrylic	100% Acrylic
Volume Solids	34% ± 2%	33% ± 2%	36% ± 2%
Solids by Weight	50% ± 2%	48% ± 2%	48% ± 2%
V.O.C.'s (Before Tinting)	<50 g/L	<100 g/L	<100 g/L
Weight per Gallon	11.0 lbs.	10.3 lbs.	10.3 lbs.
Viscosity (Before Tinting)	95 - 100 KU	95 - 100 KU	95 - 100 KU
Flashpoint	N/A	N/A	N/A
Gloss at 60°	2 - 4	8 - 10	20 - 25
Coverage per Gallon (smooth nonporous surface)	350-400 sq. ft.	350-400 sq. ft.	350-400 sq. ft.
Recommended Wet Mil Thickness	4.0	4.0	4.0
Recommended Dry Mil Thickness	1.5	1.5	1.5
MPI / Other Certifications	MPI #10	MPI #15	
Available Colors	White, tintable to over 1,000 custom colors	White, tintable to over 1,000 custom colors	White, tintable to over 1,000 custom colors
Packaging Options	1 Gallon; 5 Gallon	1 Gallon; 5 Gallon	1 Gallon; 5 Gallon

^oReported values are for white base

General Surface Preparation

Proper surface preparation is the key to any long lasting paint job. The surface to be painted must be clean and dry. Remove all dirt, dust, grease, oil, chalky residue, mildew, rust or any other surface contaminants. Use an appropriate cleaner, and then rinse thoroughly with clean water and let thoroughly dry. Special attention should be given to thoroughly wash and rinse areas under eaves and overhangs where dirt and other contaminants can collect, causing lack of adhesion. Allow several good drying days on wood or other porous surfaces before painting. Dull all glossy surfaces to create a slight profile by sanding. Remove any loose or peeling paint by sanding, scraping, wire brushing, or other practical means. Feather sand all edges to provide a smooth transition. Patch all holes with appropriate spackle or wood filler and sand smooth. Gaps between siding and windows, doors, trim, etc. can be filled with a high quality paintable caulk after priming. Most coatings failures can be attributed to inadequate surface preparation or not following application instructions.

- **Concrete / Masonry / Stucco:** New concrete and mortar must cure for a minimum of 30 days, and have a pH of less than 9. Remove all form release agents, curing compounds, efflorescence, and any other foreign materials. If painting cannot wait 30 days, then allow to dry for at least 7 days and prime with #4050 A.M.P. Acrylic Masonry Primer.
- **Cement Board Siding:** Remove all dust, dirt, efflorescence, peeling coatings, and any other foreign materials. Check the pH, if it is higher than 9, prime with #4050 A.M.P. Acrylic Masonry Primer.

.WARNING!! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application Guide

Stir contents thoroughly before and during application. Intermix containers of the same color to insure color uniformity. Apply 1 or 2 full coats as needed, keep a wet edge to avoid lap marks. Let dry thoroughly between coats. Thinning of this material is not normally required.

- **Application Tools:** High quality nylon or polyester bristle brush. High quality synthetic roller cover.
- **Airless Sprayer:** Minimum Pressure 2000 psi, .015 - .019 tip size. It is always advisable to back-roll the area to ensure proper adhesion and an even coat application. When spraying, follow spray equipment manufacturer's recommendations carefully.

Do not apply when air and substrate temperatures are below 35°F** or above 90°F.

- **Dry times:** @77°F, 50% RH – to touch 1-2 hours - to recoat 4 hours. Dry times can vary depending on temperatures, humidity, color, and film build. At temperatures below 50°F recoat times are generally 24-48 hours.
**Air and surface temperatures must remain above 35°F for a minimum of 36 hours after application. Do not apply when dew points are within 5 degrees of the temperature.
- **Cleanup:** Clean up spills or splatters immediately with soap and warm water. Clean painting tools with soap and warm water.

Not recommended for application to floors, decks or other horizontal surfaces, or to surfaces subject to immersion or prolonged contact with water. For exterior use only. **KEEP FROM FREEZING!**

Recommended Primers*		
Wood	Hirshfield's	4250 – Hirshfield's Exterior 100% Acrylic Primer Suitable exterior oil-based primer as recommended by Hirshfield's
Concrete / Masonry	Hirshfield's	1450 – Acrylic Latex Block Filler 4050 – A.M.P Acrylic Masonry Primer
Cement Board Siding	Hirshfield's	4050 – A.M.P. Acrylic Masonry Primer
Engineered Woods / Hardboard Siding	Hirshfield's	4250 - Hirshfield's Exterior 100% Acrylic Primer
Metal	Hirshfield's	Consult with your Hirshfield's representative for recommendations.

* Other primers may be appropriate. Check with your Hirshfield's representative for other recommendations. Certain colors or drastic color changes may require a gray shaded primer. Stains from water, smoke, wax bleed, grease, etc. should be sealed with an appropriate stain killing primer/sealer.

Environmental, Health & Safety Information

May cause irritation to the skin or eyes. **Use only with adequate ventilation.** Avoid prolonged breathing of vapor, spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid exposure to dust and spray mist by wearing a properly fitted and approved NIOSH respirator. Follow respirator manufacturer's directions for use. Avoid contact with the skin and eyes. Wash skin thoroughly with soap and water after handling.

When spraying be sure to follow all precautionary safety measures. Spray equipment must be handled with due care and in strict accordance with sprayer manufacturer's recommendations. Use of a NIOSH approved respirator when spraying is recommended.

Do not pour leftover material down a drain. Always recycle leftover material when possible. Consult your local sanitation department or recycling center for disposal options. Hirshfield's is a member of MN Paint Care Inc. For more information visit www.paintcare.org

First Aid Information

In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately if irritation persists. For skin contact, wash thoroughly with soap and water. Use with adequate ventilation. If you experience difficulty breathing, headache, or dizziness, leave the area and obtain fresh air. If symptoms persist, seek medical attention.

If swallowed call the POISON CONTROL CENTER, EMERGENCY ROOM, OR PHYSICIAN IMMEDIATELY.

CLOSE CONTAINER AFTER EACH USE!

KEEP OUT OF REACH OF CHILDREN!

DO NOT TAKE INTERNALLY!

For additional health and safety information refer to the Safety Data Sheet (SDS) available at www.hirshfields.com

NOTICE: The information and recommendations set forth in this document are true and correct to the best of our knowledge at the time of publication. We do not express, warrant or guarantee the accuracy, completeness, or reliability of same. Improvements in coatings technology may cause future technical data to vary from what was available when this bulletin was printed **Revised 2/15/2021.**

© Hirshfield's Paint Manufacturing, Inc. | 4450 Lyndale Avenue North, Minneapolis, MN 55412 | 1-800-432-3701

