



PARKING RAMP PAINT

1308 WHITE

General Description

A durable hi-build type finish for use on the interior of parking ramp structures and parking garages. Bright white color increases light reflectance and provides a clean, safer looking environment. Formulated for high production application by airless spray.

Physical Product Data

| | | | |
|--|---------------------|--|--|
| Product Type | Vinyl Acrylic Latex | V.O.C.'s | <50 g/L |
| Volume Solids | 39% ± 2% | Gloss at 60° | 1 -3 |
| Solids by Weight | 59% ± 2% | MPI / Other Certifications | |
| Weight per Gallon | 12.3 lbs. | Flash Point | N/A |
| Viscosity | 100 - 105 KU | Packaging Options | 5 Gallon |
| Coverage per Gallon (smooth non-porous surfaces) | 200 – 225 sq. ft. | Available Colors | White, tintable with up to 4 oz. universal colorant per gallon |
| Recommended Wet Mil Thickness (Per Coat) | 7.0 | Recommended Dry Mil Thickness (Per Coat) | 3.0 |

◇ Reported values are for white

Where to Use

This product can be used on prepared interior concrete surfaces as well as properly primed drywall, wood and metal substrates.

General Surface Preparation

Surface to be coated must be clean, dry, in sound condition, and free from all surface contaminants. Remove all dirt, dust, chalk, loose aggregate, grease, mildew, rust, etc. with appropriate cleaners, rinse, and let dry. New concrete surfaces must cure for at least 30 days and have a pH of less than 9.0. Check the pH, if it is higher than 9 prime the surface first with #4050 A.M.P. Acrylic Masonry Primer. Structural cracks must be repaired prior to applying this product.

WARNING!! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

| Recommended Primers* | | |
|----------------------|--------------|---|
| Drywall | Hirshfield's | Self priming or use 1270 – Contractor Select Zero Primer Self priming or use 1260 – Drywall Primer Sealer Self priming or use 1258 – Contractor Select PVA Drywall Primer Self priming or use 1255 – Primer Sealer PVA Drywall Primer Self priming or use 1250 – Drywall Primer Self priming or use 70150 – Premier Drywall Primer |
| Concrete / Masonry | Hirshfield's | Self priming or use 1450 – Acrylic Latex Block Filler Self priming or use 4250 – A.M.P. Acrylic Masonry Primer |
| Wood | Zinsser® | 56924972X – Smart Prime® Water-Base Primer |
| Metal | Hirshfield's | Consult with your Hirshfield's representative for recommendations |

* Other primers may be appropriate. Check with your Hirshfield's representative for other recommendations. Certain colors or drastic color changes may require a gray shaded primer. Stains from water, smoke, ink, permanent marker, grease, etc. should be sealed with an appropriate stain killing primer/sealer.

Application Guide

Stir contents thoroughly before and during application. Intermix containers of the same color to insure color uniformity.

- **Application Tools:** Airless Sprayer: Minimum Pressure 2000 psi, .017 - .021 tip size. It is always advisable to back-roll the area to ensure proper adhesion, eliminate pinholes and produce an even coat application.

Thinning is not normally required but may be necessary under certain conditions such as low humidity, or warm conditions. If needed add no more than 4 ounces of clean water per gallon.

Do not apply when air and substrate temperatures are below 50°F or above 90°F

- **Dry times:** @77°F, 50% RH – to touch 30-60 minutes - to recoat 2-4 hours. Dry times can vary depending on temperatures, humidity, color, and film build.
- **Cleanup:** Clean up spills or splatters immediately with soap and warm water. Clean painting tools with soap and warm water.

Not recommended for use in corrosive or chemical environments or for application to floors, decks or to surfaces subject to immersion or prolonged contact with water. **KEEP FROM FREEZING!**

Environmental, Health & Safety Information

May cause irritation to the skin or eyes. **Use only with adequate ventilation.** Avoid prolonged breathing of vapor, spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid exposure to dust and spray mist by wearing a properly fitted and approved NIOSH respirator. Follow respirator manufacturer's directions for use. Avoid contact with the skin and eyes. Wash skin thoroughly with soap and water after handling.

When spraying be sure to follow all precautionary safety measures. Spray equipment must be handled with due care and in strict accordance with sprayer manufacturer's recommendations. Use of a NIOSH approved respirator when spraying is recommended.

Do not pour leftover material down a drain. Always recycle leftover material when possible. Consult your local sanitation department or recycling center for disposal options. Hirshfield's is a member of MN Paint Care Inc. For more information visit www.paintcare.org

First Aid Information

In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately if irritation persists. For skin contact, wash thoroughly with soap and water. Use with adequate ventilation. If you experience difficulty breathing, headache, or dizziness, leave the area and obtain fresh air. If symptoms persist, seek medical attention.

If swallowed call the POISON CONTROL CENTER, EMERGENCY ROOM, OR PHYSICIAN IMMEDIATELY.

CLOSE CONTAINER AFTER EACH USE!

KEEP OUT OF REACH OF CHILDREN!

DO NOT TAKE INTERNALLY!

For additional health and safety information refer to the Safety Data Sheet (SDS) available at www.hirshfields.com

NOTICE: The information and recommendations set forth in this document are true and correct to the best of our knowledge at the time of publication. We do not express, warrant or guarantee the accuracy, completeness, or reliability of same. Improvements in coatings technology may cause future technical data to vary from what was available when this bulletin was printed.

REVISION DATE

1/15/2021