



Door & Trim

100% ACRYLIC ENAMEL

75290 SERIES – EGGSHELL FINISH

77290 SERIES – SATIN FINISH

78290 SERIES – SEMI-GLOSS FINISH

General Description

Door & Trim is a premium quality 100% acrylic enamel that provides a smooth, non-yellowing finish. Special anti-blocking properties prevents painted surfaces from sticking to themselves.

Where to Use

Properly prepared interior doors, trim, cabinets, etc. Can also be used as an exterior finish on entry doors, garage doors, shutters, and other such trim. Not intended for use as exterior house paint on siding surfaces.

General Surface Preparation

Surface to be coated must be clean, dry, and free from all surface contaminants including but not limited to: dust, dirt, oil, grease, mildew, and chalk. All old loose and/or peeling paint must be removed to provide a sound surface. Dull all glossy surfaces to create a slight profile by lightly sanding.

- **Wood:** Sand smooth any exposed wood, fill nail holes and any imperfections with wood filler and sand smooth. Remove all sanding dust.

Gaps between walls, ceilings, crown moldings, and other trim can be filled with a high quality, paintable, siliconized acrylic caulk after priming the surface.

Physical Product Data ⁰	75290 (Eggshell)	77290 (Satin)	78290 (Semi-gloss)
Product Type	100% Acrylic	100% Acrylic	100% Acrylic
Volume Solids	38% ± 2%	36% ± 2%	36% ± 2%
Solids by Weight	51% ± 2%	48% ± 2%	48% ± 2%
V.O.C.'s	<150 g/L	<250 g/L	<250 g/L
Weight per Gallon	10.6 lbs.	10.4lbs.	10.8 lbs.
Viscosity	95 - 100 KU	90 - 95 KU	70 - 95 KU
Flashpoint	N/A	N/A	N/A
Gloss at 60°	12 - 18	20 - 30	45 - 55
Coverage per Gallon (smooth non-porous surface)	350 - 400 sq. ft.	350 - 400 sq. ft.	350 - 400 sq. ft.
Recommended Wet Mil Thickness	3.5	4.0	3.5
Recommended Dry Mil Thickness	1.3	1.4	1.4
Available Colors	White, tintable to over 1,000 custom colors	White, tintable to over 1,000 custom colors	White, tintable to over 1,000 custom colors

⁰Reported values are for white base

WARNING!! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Recommended Primers*		
Interior Wood	Zinsser®	56924972X – Smart Prime® Water-Base Primer
Exterior Wood	Hirshfield's	4250 Housecoat Exterior 100% Acrylic Primer
Metal		Consult with your Hirshfield's representative for recommendations
Vinyl / PVC	Zinsser®	56924972X – Smart Prime® Water-Base Primer

* Other primers may be appropriate. Check with your Hirshfield's representative for other recommendations. Certain colors or drastic color changes may require a gray shaded primer. Stains from water, smoke, ink, permanent marker, grease, etc. should be sealed with an appropriate stain killing primer/sealer.

Application Guide

Stir contents thoroughly before and during application. Intermix containers of the same color to insure color uniformity. Apply 1 or 2 full coats as needed, keep a wet edge to avoid lap marks. Let dry thoroughly between coats.

- **Application Tools:** High quality nylon or polyester brush. High quality synthetic roller cover.
- **Airless Sprayer:** Minimum Pressure 2000 psi, .015 - .019 tip size. It is always advisable to back-roll the area to ensure proper adhesion and an even coat application.

Thinning is not normally required but may be necessary under certain conditions such as low humidity, or warm conditions. If needed add no more than 4 ounces of clean water per gallon.

Do not apply when air and substrate temperatures are below 50° F or above 90°F

- **Dry times:** @77°F, 50% RH – to touch 30-60 minutes - to recoat 2-4 hours. Dry times can vary depending on temperatures, humidity, color, and film build.
- **Cleanup:** Clean up spills or splatters immediately with soap and warm water. Clean painting tools with soap and warm water.

Not recommended for use in corrosive or chemical environments or for application to floors, decks or to surfaces subject to immersion or prolonged contact with water. **KEEP FROM FREEZING!**

Some exterior vinyl and PVC products have specific painting recommendations with regards to LRV (Light Reflective Values). In some cases a color with an LRV <55 may cause the product to warp. Always check with the manufacturer before selecting color.

Environmental, Health & Safety Information

May cause irritation to the skin or eyes. **Use only with adequate ventilation.** Avoid prolonged breathing of vapor, spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid exposure to dust and spray mist by wearing a properly fitted and approved NIOSH respirator. Follow respirator manufacturer's directions for use. Avoid contact with the skin and eyes. Wash skin thoroughly with soap and water after handling.

When spraying be sure to follow all precautionary safety measures. Spray equipment must be handled with due care and in strict accordance with sprayer manufacturer's recommendations. Use of a NIOSH approved respirator when spraying is recommended.

Do not pour leftover material down a drain. Always recycle leftover material when possible. Consult your local sanitation department or recycling center for disposal options. Hirshfield's is a member of MN Paint Care Inc. For more information visit www.paintcare.org

First Aid Information

In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately if irritation persists. For skin contact, wash thoroughly with soap and water. Use with adequate ventilation. If you experience difficulty breathing, headache, or dizziness, leave the area and obtain fresh air. If symptoms persist, seek medical attention.

If swallowed call the POISON CONTROL CENTER, EMERGENCY ROOM, OR PHYSICIAN IMMEDIATELY.

CLOSE CONTAINER AFTER EACH USE!

KEEP OUT OF REACH OF CHILDREN!

DO NOT TAKE INTERNALLY!

For additional health and safety information refer to the Safety Data Sheet (SDS) available at www.hirshfields.com

NOTICE: The information and recommendations set forth in this document are true and correct to the best of our knowledge at the time of publication. We do not express, warrant or guarantee the accuracy, completeness, or reliability of same. Improvements in coatings technology may cause future technical data to vary from what was available when this bulletin was printed.

Revised 1/15/2021

© Hirshfield's Paint Manufacturing, Inc. | 4450 Lyndale Avenue North, Minneapolis, MN 55412 | 1-800-432-3701